




## ARKÉ: Vertical badge switch antibact.grey

### 19465.AB

Wiring devices / Traditional wiring devices / ARKÉ / Devices

### Vertical badge switch antibact.grey




Electronic badge switch with vertical pocket, 16 A 250 V~ change-over relay output, supply voltage 230 V~ 50-60 Hz, 24 V~ 50-60 Hz and 24 Vdc (SELV), antibacterial material, grey - 3 modules. Provided without ISO card (badge)



3 - Active

1 NR

- [Light Multilanguage instructions sheet \(749 kb\)](#)
- [Full Multilanguage instructions sheet \(816 kb\)](#)



3D

- **Class group:** Alarm installations, emergency call and signalling
- **Class:** Access control system
- **Standalone:** Yes
- **Networkable:** No
- **PC-binding:** No
- **Type of interface:** None
- **Reading strategy:** Data medium
- **Signalling:** None
- **Mounting method:** Flush-mounted
- **Operating voltage AC 50 Hz:** 250,00 - 250,01 V

- **Operating voltage AC 60 Hz:** 250,00 - 250,01 V
- **Operating voltage DC:** 24,00 - 24,01 V
- **Operating temperature:** 5 - 45 °C
- **Degree of protection (IP):** IP20
- **Colour:** Grey
- **Model:** Other
- **Material:** Plastic
- **Width:** 67,50 mm
- **Height:** 49,00 mm
- **Depth:** 56,80 mm

- 00. CE Marking - EU
- 37. Marking - Morocco

- 43. UKCA mark - Great Britain
- 99. WEEE Directive ([download](#))



8007352652705  
1 NR  
5.7x5.3x7.7 [cm]  
86.9 [g]



8007352738539  
5 NR  
21.4x11.6x6 [cm]  
491.3 [g]



8007352738546  
50 NR  
30.5x25.5x22.5 [cm]  
5,253 [g]

Vimar