



ARKÉ: Rolling shutter IoT connected mechanism

19594.0

Wiring devices / View Wireless wiring devices / ARKÉ / Devices

Rolling shutter IoT connected mechanism

View Wireless connected electronic control device for 1 roller shutter with slat orientation and change-over relay output for $\cos\varphi$ 0,6 motor 2 A 100-240 V~ 50/60 Hz, local or remote control, double technology with Bluetooth® wireless technology 5.0 standard for the realization of View Wireless mesh system and Zigbee 3.0 standard, 1 input for external push button to recall a scenario, favourite position recall function, RGB LED visible in darkness with brightness control, 100-240 V 50/60 Hz power supply, to be completed with two interchangeable 1-module Arké half-buttons

- Configuration from View Wireless App for Bluetooth technology system and Amazon App for Zigbee technology
- Compatible with Alexa, Google Home and IFTTT, using the dedicated gateway or Zigbee hub
- Compatible with SmartThings hub



3 - Active

1 NR



19755.2 - 2 half buttons 1M arrows symbol grey



19755.2.B - 2 half buttons 1M arrows symbol white



19755.2.M - 2 half buttons 1M arrows symbol Metal



19597 - IoT connected gateway 2M grey





19597.B - IoT connected gateway 2M white



19597.M - IoT connected gateway 2M Metal

- [Light multilanguage instructions sheet \(940 kb\)](#)
- [Foglio istruzioni Full \(508 kb\)](#)
- [Feuille d'instructions Full \(509 kb\)](#)
- [Hoja de instrucciones Full \(507 kb\)](#)
- [Full instructions sheet \(504 kb\)](#)
- [Φυλλάδιο οδηγιών Full \(653 kb\)](#)
- [Anweisungsblatt Full \(776 kb\)](#)
- [Full \(575 kb\)](#)
- [Manuale app View Wireless \(15556 kb\)](#)
- [Manuel appli View Wireless \(37703 kb\)](#)
- [Manual app View Wireless \(37528 kb\)](#)
- [Manual View Wireless app \(37579 kb\)](#)
- [Εγχειρίδιο τεχνικού εγκατάστασης \(37781 kb\)](#)
- [Installationsanleitung View Wireless \(37508 kb\)](#)

- [Creating-the-system](#)
- [Customisations](#)
- [Operation-in-Zigbee-mode](#)
- [Bluetooth-wifi-gateway](#)



3D

- **Class group:** Domestic switching devices
- **Class:** Push button
- **Assembly arrangement:** Modular device for domestic switching devices
- **Model:** Other
- **Method of operation:** Push button
- **Number of rockers:** 1
- **Number of modules (module system):** 100
- **Number of poles:** 1
- **Nominal voltage:** 230 V
- **Rated current:** 2,00 A
- **With lighting:** Yes
- **Feedback-signal contact:** No
- **Mounting method:** Flush-mounted
- **Type of fastening:** Engage (snap)

- **Material:** Plastic
- **Material quality:** Thermoplastic
- **Surface protection:** Untreated
- **Surface finishing:** Matt
- **Colour:** Blue
- **RAL-number (similar):** 7015
- **Transparent:** No
- **Label space/information surface:** Yes
- **Imprint:** None
- **Suitable for degree of protection (IP):** IP40
- **Device width:** 22,30 mm
- **Device height:** 49,00 mm
- **Device depth:** 46,40 mm

- 00. CE Marking - EU
- 01. IMQ - Italy ([download](#))
- 06. SUBTEL - Chile ([download](#))
- 29. QCERT - Colombia
- 37. Marking - Morocco
- 37. Marking - Morocco
- 40. Bluetooth technology

- 42. Zigbee certified
- 43. UKCA mark - Great Britain
- 46. UK PSTI compliance ([download](#))
- 92. RoHS UAE
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))



8 0 0 7 3 5 2 6 2 8 5 6 4

8007352628564
1 NR
6x5.4x5.2 [cm]
52.2 [g]



8 0 0 7 3 5 2 6 2 8 5 7 1

8007352628571
60 NR
37.5x30x13.5 [cm]
3,912 [g]

Vimar