



EIKON: 1P 16AX 1-way switch 2M Next

20001.2.N




Wiring devices / Traditional wiring devices / EIKON / Devices

1P 16AX 1-way switch 2M Next

1P 16 AX 250 V~ 1-way switch, lightable, replaceable button, Next - 2 modules. Max 200 W for self-ballasted lamps (IEC 60669-1:2017)

3 - Active

20 NR



3D

- **Class group:** Domestic switching devices
- **Class:** Installation switch
- **Wiring system:** Off switch 1-pole
- **Method of operation:** Rocker/button
- **Assembly arrangement:** Modular device for domestic switching devices
- **Number of modules (module system):** 2
- **Push button switch:** Yes
- **Number of rockers:** 1
- **Mounting method:** Flush-mounted
- **Type of fastening:** Engage (snap)
- **With mounting plate:** No
- **Material:** Plastic
- **Material quality:** Thermoplastic
- **Halogen free:** Yes
- **Surface protection:** Lacquered
- **Surface finishing:** Matt

- **Colour:** Silver
- **RAL-number (similar):** 9022
- **Label space/information surface:** Yes
- **Illumination:** Optional
- **Function lighting:** Control and orientation
- **Type of lighting:** LED exchangeable
- **Suitable for degree of protection (IP):** IP40
- **Nominal voltage:** 250 V
- **Rated current:** 16,00 A
- **Feedback-signal contact:** No
- **Connection type:** Screwed terminal
- **Washing machine switch:** No
- **Device width:** 44,80 mm
- **Device height:** 49,00 mm
- **Device depth:** 36,10 mm
- **Built-in depth:** 25,00 mm

- 00. CE Marking - EU
- 01. IMQ - Italy ([download](#))
- 10. EAC Eurasian Customs Union
- 13. SNI - Indonesia
- 14. TSE - Turkey
- 15. CCC - China ([download](#))
- 19. NOM - Mexico
- 28. NSW - Australia ([download](#))
- 29. QCERT - Colombia

- 31. TISI - Thailand
- 36. ISI - India
- 37. Marking - Morocco
- 43. UKCA mark - Great Britain
- 50. Product Environm. Profile
- 92. RoHS UAE
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))



8007352285453
1 NR
5.1x4.3x5.3 [cm]
34 [g]



8007352285460
20 NR
26.9x11.6x9 [cm]
761.73 [g]



8007352643536
240 NR
38x28.5x35.5 [cm]
9,684 [g]