EIKON: 1P 20AX 1-way switch 2M white

20002.2.B

Wiring devices / Traditional wiring devices / EIKON / Devices

1P 20AX 1-way switch 2M white

1P 20 AX 250 V~ 1-way switch, lightable, replaceable button, white - 2 modules. Max 250 W for self-ballasted lamps (IEC 60669-1:2017)

3 - Active

20 NR







3D

- **Class group**: Domestic switching devices
- **Class**: Installation switch
- **Wiring system**: Off switch 1-pole
- **Method of operation**: Rocker/button
- **Assembly arrangement**: Modular device for domestic switching devices
- **Number of modules (module system)**: 2
- **Push button switch**: Yes
- **Number of rockers**: 1
- **Mounting method**: Flush-mounted
- **Type of fastening**: Engage (snap)
- **With mounting plate**: No
- **Material**: Plastic
- **Material quality**: Thermoplastic
- **Halogen free**: Yes
- **Surface protection**: Untreated
- **Surface finishing**: Matt
- **Colour**: White
- **RAL-number (similar)**: 9016
- **Label space/information surface**: Yes
- **Illumination**: Optional
- **Function lighting**: Control and orientation
- **Type of lighting**: LED exchangeable
- **Suitable for degree of protection (IP)**: IP40
- **Nominal voltage**: 250 V
- **Rated current**: 20,00 A
- **Feedback-signal contact**: No
- **Connection type**: Screwed terminal
- **Washing machine switch**: No
- **Device width**: 44,80 mm
- **Device height**: 49,00 mm
- **Device depth**: 36,80 mm
- **Built-in depth**: 25,00 mm

- 00. CE Marking - EU
- 01. IMQ - Italy (download)
- 10. EAC Eurasian Customs Union
- 19. NOM - Mexico
- 31. TISI - Thailand
- 36. ISI - India
- 37. Marking - Morocco
- 43. UKCA mark - Great Britain
- 96. Electrotechnical expert (download)
- 99. WEEE Directive (download)

8 007352 403901

8007352403901
1 NR
5.1x4.3x5.3 [cm]
34.5 [g]

8 007352 403918

8007352403918
20 NR
26.9x11.6x9 [cm]
773.1 [g]

Vimar