



EIKON: 1P 16AX reversing switch mechanism

20013.0




Wiring devices / Traditional wiring devices / EIKON / Devices

1P 16AX reversing switch mechanism

1P 16 AX 250 V~ reversing switch mechanism, lightable, to complete with 1, 2 or 3-module button. Max 200 W for self-ballasted lamps (IEC 60669-1:2017)

3 - Active

10 NR



3D

- **Class group:** Domestic switching devices
- **Class:** Installation switch
- **Wiring system:** Intermediate switch
- **Method of operation:** Rocker/button
- **Assembly arrangement:** Modular device for domestic switching devices
- **Number of modules (module system):** 1
- **Push button switch:** Yes
- **Number of rockers:** 1
- **Mounting method:** Flush-mounted
- **Type of fastening:** Engage (snap)
- **With mounting plate:** No
- **Material:** Plastic
- **Material quality:** Thermoplastic
- **Halogen free:** Yes
- **Surface protection:** Untreated
- **Surface finishing:** Matt

- **Colour:** Anthracite
- **RAL-number (similar):** 7024
- **Label space/information surface:** Yes
- **Illumination:** Optional
- **Function lighting:** Control and orientation
- **Type of lighting:** LED exchangeable
- **Suitable for degree of protection (IP):** IP40
- **Nominal voltage:** 250 V
- **Rated current:** 16,00 A
- **Feedback-signal contact:** No
- **Connection type:** Screwed terminal
- **Washing machine switch:** No
- **Device width:** 22,30 mm
- **Device height:** 49,00 mm
- **Device depth:** 34,60 mm
- **Built-in depth:** 25,00 mm

- 00. CE Marking - EU
- 01. IMQ - Italy ([download](#))
- 10. EAC Eurasian Customs Union
- 14. TSE - Turkey
- 15. CCC - China ([download](#))
- 19. NOM - Mexico
- 20. IQC - Argentina

- 28. NSW - Australia ([download](#))
- 29. QCERT - Colombia
- 36. ISI - India
- 37. Marking - Morocco
- 43. UKCA mark - Great Britain
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))



8 007352 250741
 8007352250741
 1 NR
 4.1x2.8x5.3 [cm]
 31 [g]



8 007352 250758
 8007352250758
 10 NR
 14.4x9x6 [cm]
 345.4 [g]



8 007352 640832
 8007352640832
 160 NR
 37.5x30x13.5 [cm]
 5,880 [g]