



EIKON: 2P 16AX 1-way switch +000-key white

20083.CU.B




Wiring devices / Traditional wiring devices / EIKON / Devices

2P 16AX 1-way switch +000-key white

2P 16 AX 250 V~ key-operated 1-way switch, 000 unified key removable in both positions, white. Max 200 W for self-ballasted lamps (IEC 60669-1:2017)

3 - Active

10 NR



3D

- **Class group:** Domestic switching devices
- **Class:** Installation switch
- **Wiring system:** 2-pole switch
- **Method of operation:** Key
- **Assembly arrangement:** Modular device for domestic switching devices
- **Number of modules (module system):** 1
- **Push button switch:** Yes
- **Number of rockers:** 0
- **Mounting method:** Flush-mounted
- **Type of fastening:** Engage (snap)
- **With mounting plate:** No
- **Material:** Plastic
- **Material quality:** Thermoplastic
- **Halogen free:** Yes
- **Surface protection:** Untreated
- **Surface finishing:** Matt

- **Colour:** White
- **RAL-number (similar):** 9016
- **Label space/information surface:** Yes
- **Illumination:** No
- **Function lighting:** Other
- **Type of lighting:** Other
- **Suitable for degree of protection (IP):** IP40
- **Nominal voltage:** 250 V
- **Rated current:** 16,00 A
- **Feedback-signal contact:** No
- **Connection type:** Screwed terminal
- **Washing machine switch:** Yes
- **Device width:** 22,30 mm
- **Device height:** 49,00 mm
- **Device depth:** 43,50 mm
- **Built-in depth:** 33,50 mm

- 00. CE Marking - EU
- 10. EAC Eurasian Customs Union
- 14. TSE - Turkey
- 20. IQC - Argentina
- 29. QCERT - Colombia

- 37. Marking - Morocco
- 43. UKCA mark - Great Britain
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))



8007352315877
1 NR
5.1x2.8x5.3 [cm]
55.8 [g]

8007352315884
10 NR
14.4x11.6x6 [cm]
601.3 [g]

Vimar