



EIKON: MASTER rotary dimmer 120V Next

20136.120.N

Wiring devices / Traditional wiring devices / EIKON / Devices

MASTER rotary dimmer 120V Next




Universal-dimmer, 120 V~ 60 Hz for: 40-500 W incandescent lamps, 40-300 VA electronic transformers, 10-200 W CFL lamps, 3-200 W LED lamps, LED electronic supply units, ON/OFF or built-in or from NO peripheral push buttons control, regulation by rotary potentiometer, MASTER function for 20137.120, minimum luminosity regulation, visible in darkness, Next. Not for Isoset enclosures



2 - Will be discontinued

1 NR

• [FI - Foglio istruzioni ZIS_49400635A0 \(2873 kb\)](#)




3D

- **Class group:** Domestic switching devices
- **Class:** Dimmer
- **Method of operation:** Turn button
- **Type of load:** Universal and LED Retrofit
- **Applicable with button:** Yes
- **Applicable with movement sensor:** No
- **Applicable with presence indicator:** No
- **Applicable with time switch/timer:** No
- **Applicable with transmission button:** No
- **Applicable with infrared button:** No
- **Mounting method:** Flush-mounted
- **Type of fastening:** Snapper mounting
- **Material:** Plastic
- **Material quality:** Thermoplastic
- **Surface protection:** Lacquered
- **Surface finishing:** Matt
- **Colour:** Silver
- **RAL-number (similar):** 9022
- **Transparent:** No
- **Suitable for degree of protection (IP):** IP40
- **Nominal voltage:** 120,00 - 120,01 V
- **Frequency:** 60,00 - 60,01 HZ
- **Control voltage:** 120,00 - 120,01 V
- **Connection type:** Screwed terminal
- **Device width:** 22,30 mm
- **Device height:** 49,00 mm
- **Device depth:** 61,30 mm


• 19. NOM - Mexico

• 37. Marking - Morocco



8 007352 482111

8007352482111
1 NR
5.2x3.9x6.2 [cm]
59.7 [g]



8 007352 482128

8007352482128
10 NR
20.5x11.5x7 [cm]
660 [g]

Vimar