



EIKON: TV-RD-SAT single-conn.outlet Next

20300.01.N




Wiring devices / Traditional wiring devices / EIKON / Devices

TV-RD-SAT single-conn.outlet Next

Coaxial TV-RD-SAT 5-2400 MHz socket outlet, single connection, with male connector, connection attenuation 1 dB, Next. Allows the passage of d.c. current and control signals (24 V 500 mA max)

3 - Active

20 NR



3D



- **Class group:** Antenna and satellite technique
- **Class:** Antenna socket box
- **Model:** End socket
- **Cover:** None
- **Tap loss at 860 MHz:** 0,10 dB
- **Tap loss at 2150 MHz:** 0,20 dB
- **Number of outlets:** 1

- **Suitable for remote power supply:** Yes
- **Type of fastening:** Snap mounting (engagement)
- **Colour:** Silver
- **RAL-number (similar):** 9022
- **Surface protection:** Lacquered
- **Material:** Plastic

- 00. CE Marking - EU
- 10. EAC Eurasian Customs Union
- 37. Marking - Morocco

- 43. UKCA mark - Great Britain
- 99. WEEE Directive ([download](#))



8007352287143
1 NR
4.1x2.8x5.3 [cm]
39.2 [g]

8007352287150
20 NR
21.4x11.6x6 [cm]
841 [g]

8007352634923
200 NR
30.5x25.5x22.5 [cm]
9,210 [g]

8007352750883
8,800 NR
120x80x105 [cm]
405,240 [g]