



## EIKON: LED-emergency lamp 1M 230V Next

---

### 20382.N

Wiring devices / Traditional wiring devices / EIKON / Devices

#### LED-emergency lamp 1M 230V Next

Lamp with high-efficiency LED, supply voltage 230 V~ 50-60 Hz, automatic emergency device, replaceable rechargeable Ni-MH battery, 2 hours of operating time, Next




2 - Will be discontinued

10 NR



20398 - LED auxiliary  
emergency lamp 1M

- [Multilanguage instructions sheet \(608 kb\)](#)



3D

- **Class group:** Luminaires
- **Class:** Emergency luminaire
- **Mounting method:** Built-in
- **Monitoring equipment:** None
- **With remote switch connection:** No
- **Power supply system:** Peripheral (individual battery)
- **Battery quality:** NiMH
- **Lamp type:** LED not exchangeable
- **With light source:** Yes
- **Housing material:** Plastic
- **Housing colour:** Silver

- **Material cover:** Without cover
- **Voltage type:** AC
- **Nominal voltage:** 230,00 - 230,01 V
- **Degree of protection (IP):** IP40
- **Protection class:** II
- **Max. system power:** 1,00 W
- **Rated luminous flux according to IEC 62722-2-1:** 3
- **Width:** 22,30 mm
- **Height/depth:** 47,20 mm
- **Built-in height/depth:** 37,00 mm

- 00. CE Marking - EU
- 10. EAC Eurasian Customs Union
- 37. Marking - Morocco

- 43. UKCA mark - Great Britain
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))



8007352286955  
1 NR  
5.1x2.8x5.3 [cm]  
48.27 [g]



8007352286962  
10 NR  
14.4x11.6x6 [cm]  
526.87 [g]



8007352657038  
120 NR  
36.5x33x13.5 [cm]  
6,744 [g]