



EIKON: LED auxiliary emergency lamp 1M

20398



Wiring devices / Traditional wiring devices / EIKON / Devices

LED auxiliary emergency lamp 1M

3 - Active

10 NR

- [Light multilanguage instructions sheet \(545 kb\)](#)
- [Full multilanguage instructions sheet \(1135 kb\)](#)




3D

- **Class group:** Luminaires
- **Class:** Emergency luminaire
- **Mounting method:** Surface mounting/recessed mounting
- **Function:** Escape route lighting
- **Suitable for labelling type:** Other
- **With pictogram:** No
- **Monitoring equipment:** None
- **With remote switch connection:** Yes
- **With remote control:** No
- **Power supply system:** Peripheral (individual battery)
- **Battery quality:** Lithium-ions
- **Lamp type:** LED not exchangeable
- **With light source:** Yes
- **Suitable for number of light sources:** 1
- **Lamp holder:** Other
- **Number of lighting heads:** 1
- **Housing material:** Plastic
- **Housing colour:** Grey
- **Material cover:** Without cover
- **Voltage type:** AC

- **Nominal voltage:** 100,00 - 240,00 V
- **Type of control gear:** Not required
- **Exchangeable control gear:** No
- **Light distributor:** Other
- **Degree of protection (IP):** IP40
- **Degree of protection (NEMA):** Other
- **Protection class:** II
- **Max. system power:** 1,00 W
- **Nominal operation time:** 250,00 - 251,00 h
- **Width:** 22,30 mm
- **Height/depth:** 45,70 mm
- **Length:** 49,00 mm
- **Built-in width:** 22,30 mm
- **Built-in height/depth:** 36,20 mm
- **Built-in length:** 49,00 mm
- **Type of wiring:** Ending
- **Number of poles:** 0
- **Conductor cross section:** 250
- **Connection type:** Screw connection

- 00. CE Marking - EU
- 37. Marking - Morocco
- 43. UKCA mark - Great Britain

- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))



8007352712331
1 NR
5.2x3.5x5.3 [cm]
39.35 [g]



8007352712348
10 NR
19x11.3x6.2 [cm]
450.7 [g]



8007352712355
120 NR
40x24.5x21 [cm]
5,741.4 [g]