



## EIKON: 1P+N C16 120-230V CB Next

**20405.16.N**




Wiring devices / Traditional wiring devices / EIKON / Devices

### 1P+N C16 120-230V CB Next

1P+N C 16 circuit breaker, supply voltage 120-230 V~ 50-60 Hz, breaking capacity 3000 A, Next

3 - Active

5 NR



3D

- **Class group:** Circuit breakers and fuses
- **Class:** Miniature circuit breaker (MCB)
- **Built-in depth:** 38,00 mm
- **Release characteristic:** C
- **Number of poles (total):** 2
- **Number of protected poles:** 1
- **Rated current:** 16 A
- **Rated voltage:** 230 V
- **Rated short-circuit breaking capacity Icn according to EN 60898 at 230 V:** 3,00 kA
- **Voltage type:** AC
- **Frequency:** 50 - 60 HZ
- **Current limiting class:** 1
- **Concurrently switching neutral conductor:** Yes
- **Over voltage category:** 3
- **Width in number of modular spacings:** 1
- **Degree of protection (IP):** IP40

- 00. CE Marking - EU
- 01. IMQ - Italy ([download](#))
- 37. Marking - Morocco

- 43. UKCA mark - Great Britain
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))



8007352286382  
1 NR  
6x2.8x5.3 [cm]  
55.27 [g]



8007352286399  
5 NR  
14.2x6.7x5.9 [cm]  
308.2 [g]

Vimar