



EIKON: Vertical badge switch 2M grey

20463

Wiring devices / Traditional wiring devices / EIKON / Devices

Vertical badge switch 2M grey




Upright electronic badge switch, 4 A 250 V~ NO (NON SELV) change-over relay output, power supply 120-230 V~ 50-60 Hz, slot lighting for location in the dark, trimmer for regulating switch-off time after removing the card, grey - 2 modules. Supplied without ISO card (badge)



3 - Active

1 NR

- [Multilanguage instructions sheet \(1182 kb\)](#)



3D

- **Class group:** Alarm installations, emergency call and signalling
- **Class:** Access control system
- **Standalone:** Yes
- **Networkable:** No
- **PC-binding:** No
- **Type of interface:** None
- **Reading strategy:** Data medium
- **Signalling:** None
- **Mounting method:** Flush-mounted

- **Operating voltage AC 50 Hz:** 250,00 - 250,01 V
- **Operating voltage AC 60 Hz:** 250,00 - 250,01 V
- **Operating temperature:** 5 - 35 °C
- **Degree of protection (IP):** IP20
- **Colour:** Grey
- **Material:** Plastic
- **Width:** 44,80 mm
- **Height:** 49,00 mm
- **Depth:** 43,50 mm

- 00. CE Marking - EU
- 37. Marking - Morocco

- 43. UKCA mark - Great Britain
- 99. WEEE Directive ([download](#))



8007352561403
1 NR
5.2x5.7x7.6 [cm]
69.9 [g]



8007352563780
5 NR
21.4x11.6x6 [cm]
407.3 [g]



8007352726147
50 NR
30.5x25.5x22.5 [cm]
4,073 [g]

Vimar