



## EIKON: 16 A IoT connected actuator grey

**20593**

Wiring devices / View Wireless wiring devices / EIKON / Devices

### 16 A IoT connected actuator grey

View Wireless connected electronic control device with NO 16 A 100-240 V~ 50/60 Hz relay output, local control with push button or remote control, double technology with Bluetooth® wireless technology 5.0 standard for the realization of View Wireless mesh system and Zigbee 3.0 standard, function for measuring the instant power and load cut-off threshold, RGB LED visible in darkness with brightness control, 100-240 V 50/60 Hz power supply, grey

- Configuration from View Wireless App for Bluetooth technology system and Amazon App for Zigbee technology
- Compatible with Alexa, Google Home and IFTTT, using the dedicated gateway or Zigbee hub
- Compatible with SmartThings hub



3 - Active


1 NR



20597 - IoT connected gateway 2M grey





20203 - 2P+E 16A P17/11 outlet grey



03925 - Bluetooth Low Energy RF device

- Light Multilanguage instructions sheet (1031 kb)
- Foglio istruzioni Full (550 kb)
- Feuille d'instructions Full (548 kb)
- Hoja de instrucciones Full (546 kb)
- Full instructions sheet (544 kb)
- Φυλλάδιο οδηγιών Full (720 kb)
- Anweisungsblatt Full (547 kb)
- Full (610 kb)
- Manuale app View Wireless (15556 kb)
- Manuel appli View Wireless (37703 kb)
- Manual app View Wireless (37528 kb)
- Manual View Wireless app (37579 kb)
- Εγχειρίδιο τεχνικού εγκατάστασης (37781 kb)
- Installationsanleitung View Wireless (37508 kb)

- Creating-the-system
- Customisations
- Operation-in-Zigbee-mode
- Bluetooth-wifi-gateway



3D



- **Class group:** Installation bus systems
- **Class:** Switch actuator for bus system
- **Bus system KNX:** No
- **Bus system KNX-RF (Radio Frequent):** No
- **Bus system radio frequent:** Yes
- **Bus system LON:** No
- **Bus system Powernet:** No
- **Other bus systems:** None
- **Radio frequent bidirectional:** Yes
- **Mounting method:** Flush-mounted
- **Width in number of modular spacings:** 1

- **Local operation/hand operation:** Yes
- **With LED indication:** Yes
- **Suitable for C-load:** Yes
- **Max. number of switching contacts:** 1
- **Rated current:** 16 A
- **Rated operating voltage:** 100,00 - 240,00 V
- **Different phases connectable:** No
- **With bus connection:** Yes
- **Modular expandability:** No
- **Degree of protection (IP):** IP40

- 00. CE Marking - EU
- 01. IMQ - Italy ([download](#))
- 19. NOM - Mexico
- 29. QCERT - Colombia
- 37. Marking - Morocco
- 40. Bluetooth technology

- 42. Zigbee certified
- 43. UKCA mark - Great Britain
- 92. RoHS UAE
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))



8 007352628489

8007352628489  
1 NR  
5.2x3.5x5.3 [cm]  
56 [g]



8 007352628496

8007352628496  
60 NR  
27x23x12.5 [cm]  
3,526 [g]

Vimar