



EIKON: Rolling shutter IoT connected mechanism

20594.0

Wiring devices / View Wireless wiring devices / EIKON / Devices

Rolling shutter IoT connected mechanism

View Wireless connected electronic control device for 1 roller shutter with slat orientation and change-over relay output for $\cos\phi$ 0,6 motor 2 A 100-240 V~ 50/60 Hz, local or remote control, double technology with Bluetooth® wireless technology 5.0 standard for the realization of View Wireless mesh system and Zigbee 3.0 standard, 1 input for external push button to recall a scenario, favourite position recall function, RGB LED visible in darkness with brightness control, 100-240 V 50/60 Hz power supply, to be completed with two interchangeable 1-module Eikon half-buttons

- Compatible with Alexa, Google Home and IFTTT, using the dedicated gateway or Zigbee hub
- Compatible with SmartThings hub



3 - Active

1 NR



20755.2 - 2 half buttons 1M arrows symbol grey



20755.2.B - 2 half buttons 1M arrows symbol white



20755.2.N - 2 half buttons 1M arrows symbol Next



20597 - IoT connected gateway 2M grey






20597.B - IoT connected gateway 2M white



20597.N - IoT connected gateway 2M Next

- Light multilanguage instructions sheet (940 kb)
- Foglio istruzioni Full (508 kb)
- Feuille d'instructions Full (509 kb)
- Hoja de instrucciones Full (507 kb)
- Full instructions sheet (504 kb)
- Φυλλάδιο οδηγιών Full (653 kb)
- Anweisungsblatt Full (776 kb)
- Full (575 kb)
- Manuale app View Wireless (15556 kb)
- Manuel appli View Wireless (37703 kb)
- Manual app View Wireless (37528 kb)
- Manual View Wireless app (37579 kb)
- Εγχειρίδιο τεχνικού εγκατάστασης (37781 kb)
- Installationsanleitung View Wireless (37508 kb)

- Creating-the-system
- Customisations
- Operation-in-Zigbee-mode
- Bluetooth-wifi-gateway



3D



- **Class group:** Domestic switching devices
- **Class:** Push button
- **Assembly arrangement:** Modular device for domestic switching devices
- **Model:** Other
- **Method of operation:** Push button
- **Number of rockers:** 1
- **Number of modules (module system):** 100
- **Number of poles:** 1
- **Nominal voltage:** 230 V
- **Rated current:** 2,00 A
- **With lighting:** Yes
- **Feedback-signal contact:** No
- **Mounting method:** Flush-mounted
- **Type of fastening:** Engage (snap)
- **Material:** Plastic
- **Material quality:** Thermoplastic
- **Surface protection:** Untreated
- **Surface finishing:** Matt
- **Colour:** Anthracite
- **RAL-number (similar):** 7024
- **Transparent:** No
- **Label space/information surface:** Yes
- **Imprint:** None
- **Suitable for degree of protection (IP):** IP40
- **Device width:** 22,30 mm
- **Device height:** 49,00 mm
- **Device depth:** 46,90 mm

- 00. CE Marking - EU
- 01. IMQ - Italy ([download](#))
- 06. SUBTEL - Chile
- 37. Marking - Morocco
- 37. Marking - Morocco
- 40. Bluetooth technology

- 42. Zigbee certified
- 43. UKCA mark - Great Britain
- 92. RoHS UAE
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))



8007352628588
1 NR
6x5.4x5.2 [cm]
52.2 [g]



8007352628595
60 NR
37.5x30x13.5 [cm]
3,912 [g]

Vimar