



## Shared A/V components: 2F+ LSZH cable 2x1 outer laying Eca 100m

### 732I.E.100

ELVOX Door entry system / 2F/2F+ video door entry system / Shared A/V components / A/V cables

### 2F+ LSZH cable 2x1 outer laying Eca 100m

Due Fili Plus cable for internal/external laying, 2x1 mm<sup>2</sup> twisted conductors, with insulation and LSZH sheath, Eca class, operating temperature -25/+70 °C, insulation degree 600/1000 V, suitable for laying underground in dry ducting or channels with efficient drainage (max. 24hrs wet), not suitable for laying directly underground, suitable for installation with category I energy cable (U<sub>0</sub> = 400 V), green - 100 m bundle



3 - Active

100 M

- **Class group:** Communication technique
- **Class:** Accessories/spare parts for door communication
- **Suitable for:** Outdoor station

- **Mounting method:** Flush-mounted
- **Material:** Other
- **Colour:** Green

- 00. CE Marking - EU ([download](#))
- 00. CE Marking - EU ([download](#))

- 43. UKCA mark - Great Britain



8 0 1 3 4 0 6 3 0 1 2 2 2  
8013406301222  
1 M  
100x0.6x0.6 [cm]  
68.08 [g]



8 0 1 3 4 0 6 3 0 1 2 3 9  
8013406301239  
100 M  
30x30x12 [cm]  
6,808 [g]



8 0 1 3 4 0 6 3 0 3 1 1 0  
8013406303110  
200 M  
29x28.5x24.5 [cm]  
14,560 [g]

Vimar