



Motors: HIDDY200D undergr. operator 24V 2m 200kg

EIM1

Safety / ELVOX Automations / Motors / Hinged

HIDDY200D undergr. operator 24V 2m 200kg

HIDDY 200D non-reversible 24 V electromechanical underground operator for swing gates with leaves up to 2 m and 200 kg, residential use, magnetic encoder, supplied with 2 m of cable



3 - Active

1 NR

- [Esploso serie HIDDY 200D - EN \(70 kb\)](#)
- [Multilanguage installer manual \(5157 kb\)](#)

- **Class group:** Gate operators, pumps and ventilators
- **Class:** Swing gate operator
- **Model:** One-wing, left and right
- **Max. width of door/gate wing:** 2.000 mm
- **Max. weight of door/gate leaf:** 200 kg
- **Type of current:** DC
- **Motor voltage:** 24 V

- **Limit switch:** Internal end switch
- **With motor control unit:** No
- **With post fittings:** No
- **With wing fittings:** No
- **With key-switch:** No
- **With radio receiver:** No

- 00. CE Marking - EU
- 37. Marking - Morocco

- 43. UKCA mark - Great Britain
- 99. WEEE Directive ([download](#))



8013406228192
1 NR
43.7x16x16 [cm]
8,184 [g]

Vimar