



Kits: EKKO 400D linear kit 24V 4m 250kg

EK07.S.W.EXP.120

Safety / ELVOX Automations / Kits / Hinged

EKKO 400D linear kit 24V 4m 250kg

EKKO 400D kit for swing gate leaves up to 4 m, 250 kg. Contents: 1 EAM3 EKKO 400D non-reversible 24 V electromechanical linear actuator, 1 ECA5.W 24 V control unit with display designed for communication with Smartphone and Tablet, 1 ELA5 12/24 V flashing LED with built-in aerial, 2 ETRN4 4-channel 433 MHz rolling code remote controls, 1 EFA1 pair of 180° adjustable photocells, 1 ZX20 warning sign. 120 V power supply



2 - Will be discontinued

1 NR



EAM3 - EKKO 400D linear operator 24V 4m 250kg



ECA5.W - Wi-Fi control card 24V swing gate



ELA5 - Flashing light LED 12/24Vdc



ETRN4 - 4-channel remote control 433MHz rolling



EFA1 - Pair of 12/24V 110mA 180° photocells 15m



ZX20 - Warning sign

- [Multilanguage instructions sheet \(510 kb\)](#)
- [Installer manual \(1763 kb\)](#)
- [Manuale installatore \(1165 kb\)](#)
- [Manuel installateur \(1163 kb\)](#)
- [Manual del instalador \(1166 kb\)](#)
- [Installer manual \(1161 kb\)](#)
- [Εγχειρίδιο τεχνικού εγκατάστασης \(1169 kb\)](#)
- [Installationsanleitung \(1168 kb\)](#)

- **Class group:** Gate operators, pumps and ventilators
- **Class:** Swing gate operator
- **Model:** 2 wings
- **Max. width of door/gate wing:** 4.000 mm
- **Max. weight of door/gate leaf:** 550 kg
- **Type of current:** DC
- **Motor voltage:** 24 V

- **Limit switch:** Internal end switch
- **Frequency radio receiver:** 433 MHz
- **With motor control unit:** Yes
- **With post fittings:** Yes
- **With wing fittings:** Yes
- **With key-switch:** Yes
- **With radio receiver:** Yes

- 00. CE Marking - EU
- 37. Marking - Morocco

- 43. UKCA mark - Great Britain
- 99. WEEE Directive ([download](#))



8013406306722
1 NR
97x30x31 [cm]
16,350 [g]