



## Motors: Tubular rolling shutter motor 230V~ 40kg

---

### EV45S40

Safety / ELVOX Automations / Motors / Windows and doors

#### Tubular rolling shutter motor 230V~ 40kg

230 V~ tubular motor for roller shutters, lifting capacity 40 kg, residential, commercial and tertiary use, 60 mm octagonal adaptors, complete with fixing brackets


- Complete with fixing brackets
- For use in the following sectors: residential, commercial and services
- Automations for roller shutters and sun awnings Every single roller shutter can be automated extremely simply, and can be controlled from a single point, usually positioned next to the roller shutter or incorporated into the home automation scenarios of the smart home
- IP 44 protection degree



3 - Active

1 NR

- [Installer manual \(10138 kb\)](#)



- **Class group:** Gate operators, pumps and ventilators
- **Class:** Tube mounted motor
- **Outer diameter:** 45 mm
- **Moment of torque:** 20 N/m
- **For roller blinds:** Yes
- **For awnings:** No
- **Max. weight of roller shutter:** 40 kg

- **Type of end switch:** Mechanical
- **Back jump:** No
- **Electronic route monitoring:** No
- **Electronic obstacle recognition:** No
- **With carrier:** Yes
- **With shaft adapter:** Yes
- **Length:** 494 mm

- 00. CE Marking - EU
- 43. UKCA mark - Great Britain

- 99. WEEE Directive ([download](#))



8013406262448  
1 NR  
51.5x8x8 [cm]  
2,465 [g]



8007352668362  
4 NR  
53.5x34x10 [cm]  
9,860 [g]



8013406304766  
5 NR  
53.5x44x10 [cm]  
12,800 [g]