



## Connector block boxes: Flush mounting box 4M light blue

---

### V71304

System infrastructure / Enclosures and control units / Connector block boxes  
/ Flush mounting

#### Flush mounting box 4M light blue

4-module flush mounting box, (Glow Wire 650 °C), for masonry walls, light blue

- Plenty of space of internal wiring
- Wide range of accessories available: anti-mortar covers, coupling joints to create multiple series of boxes
- Knockouts designed for the insertion of pipes with various cross-sections
- Rack for fixing the dividing screen (patented)
- Fixing lug of the support screws with zinc-plating treatment to prevent the thread from clogging during installation and favour screwing



3 - Active


6 NR



V71304.AU - Flush mounting box 4M black



V71324 - Antimortar cover for flush-mount box 4M





V71634 - Flat cover 4M



V71550 - Dividing screen for flush-mount box yell



V71563 - Joint plate for flush-mount boxes yellow



3D

- **Class group:** Connection material (electrotechnical)
- **Class:** Box/housing for built-in mounting in the wall/ceiling
- **Mounting method:** Flush-mounted
- **Shape:** Rectangular
- **Construction type:** Device connection box (round/square)
- **Model:** Other
- **Provided with revolving ring:** No
- **Couplable:** Yes
- **Equipped with:** None
- **Diameter:** 0 mm
- **Length:** 59,00 mm
- **Width:** 121,00 mm
- **Depth:** 0,00 - 49,80 mm
- **Inner depth:** 50,00 mm
- **For number of electric fittings:** 4
- **Mounting switching equipment:** Screwing
- **With screws:** No
- **Housing feed-through by break-out opening:** Yes
- **Housing feed-through by seal membrane:** No
- **Housing feed-through by nozzle:** No
- **Housing feed-through by step membrane:** No
- **For tube diameter:** 20/25 mm
- **Pipe locking:** No

- **Pipe locking optional:** No
- **Inlet from the rear:** Yes
- **Number of inlets:** 14
- **Number of included spouts:** 0
- **Material:** Plastic
- **Halogen free:** Yes
- **Surface protection:** Untreated
- **Colour:** Blue
- **Degree of protection (IP):** IP00
- **Cover model:** None
- **Transparent cover:** No
- **Cover attachment:** Screwed
- **Sealable:** No
- **Circuit integrity:** None
- **With screening:** No
- **Air tight:** No
- **Max. conductor cross section:** 0
- **Number of poles of the clamp:** 0
- **Clamp position fixed:** No
- **Luminaire hook mounting:** No
- **Nozzle:** None
- **Special application:** None

- 00. CE Marking - EU
- 01. IMQ - Italy ([download](#))
- 15. CCC - China ([download](#))

- 43. UKCA mark - Great Britain
- 50. Product Environm. Profile
- 96. Electrotechnical expert ([download](#))



8007352079403  
1 NR  
13.1x6.9x5 [cm]  
38.2 [g]



8007352079410  
6 NR  
13.1x6.9x30 [cm]  
238.27 [g]



8007352079427  
96 NR  
59.5x38.5x26.5 [cm]  
4,595.33 [g]



8007352356245  
2,304 NR  
80x120x180 [cm]  
115,000 [g]