



Connector block boxes: Flush-mount box 8M f/hollow walls blue

V71718

System infrastructure / Enclosures and control units / Connector block boxes / Flush mounting

Flush-mount box 8M f/hollow walls blue

8-module mounting box (GW 850 °C), for hollow walls, light blue


- Suitable for several types of hollow walls (e.g. plasterboard, wood, plastic laminate or similar)
- Preparation of the hole with a hollow cutter with a diameter of 68 mm.
 Hole centring plate incorporated into the back
- Improved retention knockouts, designed for the insertion of pipes with various cross-sections (16, 20 or 25 mm) and metal fins for surface mounting the box on walls with a variable thickness of between 1 and 38 mm
- Fixing lugs for support screws made of metal
- Wide range of accessories available: accessories with a template function for tracing the hole, with joining function for mounting in series and installation on the inside of the wall; internal partitions; decorative covers





3 - Active

10 NR

Tutorial ISOBOX EN







3D

Class group: Connection material (electrotechnical)

Class: Box/housing for built-in mounting in the wall/ceiling

Mounting method: Hollow wall

Shape: Rectangular

Construction type: Device connection box (round/square)

Model: Other

Provided with revolving ring: No

Couplable: Yes

• Equipped with: None

• Diameter: 0 mm

Length: 138,00 mm

• Width: 138,00 mm • Depth: 0,00 - 56,00 mm

Inner depth: 50,00 mm

For number of electric fittings: 8

Mounting switching equipment: Screwing

With screws: No

A Housing feed-through by break-out opening: Yes

Housing feed-through by seal membrane: No

Housing feed-through by nozzle: No

Housing feed-through by step membrane: No

For tube diameter: 20/25 mm

Pipe locking: No

Pipe locking optional: No

Inlet from the rear: Yes

Number of inlets: 16

Number of included spouts: 0

Material: Plastic

Halogen free: Yes

Surface protection: Untreated

Colour: Blue

Degree of protection (IP): IP00

Cover model: None
Transparent cover: No

Cover attachment: Screwed

Sealable: No

Circuit integrity: None

With screening: No

Air tight: No

• Max. conductor cross section: 0

Number of poles of the clamp: 0

Clamp position fixed: No

Luminaire hook mounting: No

Nozzle: None

Special application: None

• 01. IMQ - Italy (download)

15. CCC - China (download)

96. Electrotechnical expert (download)





8007352425781 1 NR 13.8x13.8x5.6 [cm] 80 [g]

8007352425798 10 NR 30.5x26x22 [cm] 1,116 [g]

Vimar